

Nawkaw
AUSTRALIA
CONCRETE AND MASONRY STAINS

**TECHNICAL
DATA SHEET**

**Nawkaw
Graffiti Remover**

Nawkaw Graffiti Remover allows the easy removal of graffiti on off form concrete with below nominated coatings.

Product Properties:

- Environmentally responsible – biodegradable, environmentally friendly
- Not caustic
- Simple to use
- Versatile - can be used at temperatures between 5°C -50°C
- Minimal smell
- Removes graffiti quickly without effecting the surface

Coverage Treatment Yield:

Approx. 10-12m² per litre depending on porosity of substrate formulation and age of the graffiti.

Suitable Surfaces:

The Nawkaw Graffiti Remover is suitable for off form concrete that has been coated with:

- NawTone K mineral stain followed by protective Photocatalyst Coatings ecotio₂[®]
- Protective Photocatalyst Coatings coating ecotio₂[®]

Preparation and Application Procedure:

Prior to application ensure that you have read through the product Safety Data Sheet and label. The substrate is to be dry & free of dust. It is important to start with a small test area. Only work small areas at a time, from top to bottom, to avoid run off on already completed sections.

1. Apply the product via spray application. Do not apply to a large area, work in small sections
2. Allow the Graffiti Remover to react and soften the graffiti, about 30 seconds. Do not leave the Nawkaw Graffiti Remover longer than 30 seconds before rinsing off. Do not allow it to dry out
3. Rinse off with water via hose or water jet
4. Pat surface and allow to dry
5. Repeat steps 2-5 above, as necessary, until satisfactory removal has been reached. It is important to dry up the surface between every treatment
6. Wash clean with water afterwards

Please note that very thick, old or hardened graffiti can require more than one treatment.

Graffiti Removal Methods to be Strictly Avoided:

- Pressure washing
- Mechanical scraping, sanding or abrasive tag removal
- Maintenance cleaning using strong acids or alkalis or products containing ammonia
- Any method other than the method described above
- Graffiti removal by materials and techniques that do not strictly follow this procedure may void the any warranty given